



# HUMIDITY/TEMPERATURE TRANSMITTERS

Passive Temperature Outputs, Sintered Filter Options

CALIBRATION SERVICES AVAILABLE



Sintered filter version




OSA (outside air)



Duct mount

Duct sintered



The Series RHP Temperature and Humidity Transmitters combine the voltage or current humidity transmitter output with a passive temperature thermistor or RTD output. Featuring polymer capacitance humidity sensors, models are available with 2%, 3% or 5% accuracies. Duct mounted transmitters are available with an optional two-line alpha numeric LCD display.

**FEATURES/BENEFITS**

- 2%, 3%, or 5% accuracy models
- Optional LCD display on duct mount models
- Radiation shield option for outdoor installation in direct sunlight

**APPLICATIONS**

- Air economizers
- Outdoor temperature and relative humidity reference
- Pool room humidity monitoring

| MODEL CHART        |     |             |                       |             |  |             |   |  |
|--------------------|-----|-------------|-----------------------|-------------|--|-------------|---|--|
| Example            | RHP | -2          | D                     | 1           | A  | -LCD        | RHP-2D1A-LCD  | Price  |
| Series             | RHP |             |                       |             |  |             | RH/passive temperature sensor transmitter   | -  |
| Accuracy           |     | 2<br>3<br>5 |                       |             |  |             | 2% accuracy<br>3% accuracy<br>5% accuracy   | +\$30.25<br>+24.75<br>-  |
| Housing Type       |     |             | D<br>M<br>O<br>S<br>R |             |  |             | Duct mount with membrane filter<br>Duct mount with HDPE filter<br>OSA (outside air)<br>OSA with sintered filter*<br>Radiation shield  | 101.00<br>101.00<br>98.00<br>103.00<br>160.00  |
| RH Output          |     |             |                       | 1<br>2<br>3 |  |             | 4-20 mA<br>0-10 V<br>0-5 VDC  | -<br>-<br>-  |
| Temperature Sensor |     |             |                       |             | 0<br>1<br>2<br>3<br>A<br>B<br>C<br>D<br>E<br>F |             | None<br>4-20 mA<br>0-10 VDC<br>0-5 VDC<br>10K @ 25°C thermistor type III<br>10K @ 25°C thermistor type II<br>3K @ 25°C thermistor<br>100 Ω RTD DIN 385<br>1K Ω RTD DIN 385<br>20K Ω @ 25°C thermistor | -10.00<br>+10.50<br>+10.50<br>+10.50<br>+5.20<br>+5.20<br>+6.20<br>+6.20<br>+6.20<br>+5.20 |
| Options            |     |             |                       |             |  | LCD<br>NIST | LCD display<br>NIST traceable calibration certificate   | +52.00<br>+121.00(®)   |

\*Use OSA with sintered filter models when purchasing Series RHRS radiation shield separately.

(®) Items are net priced and are not subject to any discount.

**SPECIFICATIONS**

**Relative Humidity Range:** 0 to 100% RH.  
**Temperature Range:** -40 to 140°F (-40 to 60°C).  
**Accuracy, RH:** RHP-2XXX ±2% 10-90% RH @ 25°C; RHP-3XXX ±3% 20-80% RH @ 25°C; RHP-5XXX ±5% 20-80% RH @ 25°C.  
**Accuracy, Thermistor Temp Sensor:** ±0.2°C @ 25°C (±0.36°F @ 77°F).  
**Accuracy, RTD Temp Sensor:** DIN Class B; ±0.3°C @ 0°C (±0.54°F @ 32°F).  
**Accuracy, Solid State Band Gap:** ±0.9°F @ 77°F (±0.3°C @ 25°C).  
**Hysteresis:** ±1%.  
**Repeatability:** ±0.1% typical.  
**Temperature Limits:** -40 to 140°F (-40 to 60°C).  
**Storage Temperature:** -40 to 176°F (-40 to 80°C).  
**Compensated Temperature Range:** -4 to 140°F (-20 to 60°C).  
**4 to 20 mA Loop Powered Models:** Power requirements: 10-35 VDC; Output signal: 4-20 mA.  
**0-5/10V Output Models:** Power requirements: 15-35 VDC or 15-29 VAC; Output signal: 0-10 V @ 5 mA max.  
**Solid State Band Gap Temperature Sensor Output Ranges:** Switch selectable, -20 to 140°F (-28.9 to 60°C); 0 to 100°F (-17.8 to 37.8°C); 40 to 90°F (4.4 to 32.3°C); -4 to 140°F (-20 to 60°C).  
**Response Time:** 15 s.  
**Electrical Connections:** Removable screw terminal block.  
**Conduit Connection:** Duct mount: 1/2" NPS; OSA: 1/2" (22.3 mm).  
**Drift:** < 1% RH/year.  
**RH Sensor:** Capacitance polymer.  
**Temperature Sensor:** Types 1, 2, 3: Solid state band gap; Curves A, B, C: Thermistor; Curves D, E: Platinum RTD DIN 385.  
**Enclosure:** Duct mount: PBT; OSA: Polycarbonate.  
**Enclosure Rating:** Duct mount: NEMA 4X (IP66) for housing only; OSA: NEMA 4X (IP66).  
**Display:** Duct mount only, optional 2-line alpha numeric, 8 characters/line.  
**Display Resolution:** RH: 0.1%; 0.1°F (0.1°C).  
**Weight:** Duct mount: .616 lb (.3 kg); OSA: 1 lb (.45 kg).  
**Agency Approvals:** CE.