




SERIES 616KD | DIFFERENTIAL PRESSURE TRANSMITTER ± 0.25 , ± 1 OR 2% ACCURACY



FEATURES/BENEFITS

- Simple calibration push-button sets back zero and span, saving time installing and over the service life
- Cost effective and compact device suitable for OEM applications where space, simplicity, and value are key
- Ranges and accuracy selection cover a wide range of applications minimizing components and determining standardizing on design
- Optional plenum rated units meeting UL Standard 2043 are available

APPLICATIONS

- Air handlers
- Duct pressure
- Variable air volume
- Filter monitoring


DESCRIPTION

The **Series 616KD Differential Pressure Transmitters ± 0.25 , ± 1 or 2% Accuracy** are designed for simplicity, making them the ideal choice for installers and maintenance professionals. These instruments not only alleviate cumbersome turn pots typically found in most transmitters, but eliminate entirely the need to span the instruments during calibration. With single digital push button, both ZERO AND SPAN are calibrated properly, nothing else is required. No additional reference pressure sources or separate calibration devices are necessary.

SPECIFICATIONS

Service	Air and non-combustible, compatible gases.
Wetted Materials	Consult factory.
Accuracy	616KD-A: $\pm 0.25\%$ FS; 616KD-B: $\pm 1\%$ FS, 616KD: $\pm 2\%$ FS.
Stability	$\pm 1\%$ FS/year.
Temperature Limits	0 to 140°F (-17.8 to 60°C).
Compensated Temperature Range	20 to 122°F (-6.67 to 50°C).
Pressure Limits	2 psig (ranges 5 in w.c. or lower); 5 psig (ranges 10 to 40 in w.c.).
Thermal Effect	616KD-A: $\pm 0.02\%$ FS/°F; 616KD-B: $\pm 0.04\%$ FS/°F; 616KD: $\pm 0.06\%$ FS/°F, includes zero and span.
Power Requirements	4-20 mA output: 10 - 35 VDC (2 wire) or 12-26 VAC (4 wire); 5V output: 10-35 VDC (3 wire) or 12-26 VAC (4 wire); 10V output: 13-35 VDC (3 wire) or 12-26 VAC (4 wire) for 616KD A and B. 16 to 36 VDC (2 or 3 wire): 20 to 28 VAC (3 wire) for 616KD.
Output Signal	4 to 20 mA or option with field selectable 0-10, 0-5, 2-10, 1-5 volts.
Zero and Span Adjustments	Push button.
Loop Resistance	4-20 mA output (DC): 0 - 1250 Ω max. $R_{max} = 50(V_{psDC} - 10) \Omega$; 4-20 mA output (AC): 0 - 1200 Ω max. $R_{max} = 50(1.4 V_{psAC} - 12) \Omega$; Voltage output: 5K Ω minimum.
Current Consumption	24 mA max for 616KD A and B. 21 mA max for 616KD.
Electrical Connections	Screw-type terminal block.
Process Connections	Barbed, dual size to fit 1/8" & 3/16" (3 mm and 5 mm) ID rubber or vinyl tubing.
Enclosure Rating	NEMA 1 (IP20).
Mounting Orientation	Vertical with pressure connections pointing down.
Weight	1.8 oz (51 g).
Agency Approvals	CE, optional plenum rated units meet UL Standard 2043.

DIMENSIONS



HOW TO ORDER

Use the **bold** characters from the chart below to construct a product code.

	616KD	-A	-12	-AT	
SERIES					OPTIONS
616KD: Differential pressure transmitter					-AT: Aluminum tag
ACCURACY					-FC: Factory calibration
-A: 0.25% full-scale accuracy					-NIST: NIST certification
-B: 1.0% full-scale accuracy					-TC: Terminal cover
: 2.0% full-scale accuracy					-V: Voltage output 0-5, 1-5, 0-10, 2-10 VDC (field selectable)
Note: 0.25% FS accuracy is not available in the following ranges 00, 01, 10, 11.					-PR: Plenum rated
					RANGE
					-00: 0 to 1 in w.c.
					-01: 0 to 2 in w.c.
					-02: 0 to 3 in w.c.
					-03: 0 to 5 in w.c.
					-04: 0 to 10 in w.c.
					-05: 0 to 15 in w.c.
					-06: 0 to 20 in w.c.
					-07: 0 to 25 in w.c.
					-08: 0 to 40 in w.c.
					-10: 0 to 250 Pa
					-11: 0 to 500 Pa
					-12: 0 to 750 Pa
					-13: 0 to 1250 Pa
					-14: 0 to 2500 Pa
					-15: 0 to 5000 Pa
					-50: 0 to ± 1 in w.c.
					-51: 0 to ± 2 in w.c.
					-57: 0 to ± 3 in w.c.
					-52: 0 to ± 5 in w.c.
					-53: 0 to ± 10 in w.c.
					-54: 0 to ± 250 Pa
					-55: 0 to ± 500 Pa
					-56: 0 to ± 750 Pa
					-58: 0 to ± 1250 Pa

ORDER ONLINE TODAY!

dwyer-inst.com/Product/Series616KD



DWYER INSTRUMENTS, INC.

©Copyright 2019 Dwyer Instruments, Inc.
Printed in U.S.A. 7/19

DS-616KD Rev. 3

Important Notice: Dwyer Instruments, Inc. reserves the right to make changes to or discontinue any product or service identified in this publication without notice. Dwyer advises its customers to obtain the latest version of the relevant information to verify, before placing any orders, that the information being relied upon is current.