



Model 6250

Accurate with results within **0.05%**

► SPECIFICATIONS

| MODEL | 6250 | | | | | | |
|-------------------------|--|------------------------|-------------------------|--------------------------|------------------------|-------------------------|--------------------------|
| Range | 5.0000 mΩ | 25.000 mΩ | 250.00 mΩ | 2500.0 mΩ | 25.000 Ω | 250.00 Ω | 2500.0 Ω |
| Accuracy | 0.15% of Reading + 1.0μΩ | 0.05% of Reading + 3μΩ | 0.05% of Reading + 30μΩ | 0.05% of Reading + 0.3mΩ | 0.05% of Reading + 3mΩ | 0.05% of Reading + 30mΩ | 0.05% of Reading + 300mΩ |
| Resolution | 0.1μΩ | 1μΩ | 10μΩ | 0.1mΩ | 1mΩ | 10mΩ | 100mΩ |
| Test Current | 10A | 10A | 10A | 1A | 100mA | 10mA | 1mA |
| Measurement Mode | Selectable: Inductive (continuous test), Resistive (instantaneous test) or Auto (multiple tests) | | | | | | |
| Metal Type Alpha | Selectable: Copper, Aluminum or Other Metal Programmable from 000.00 to 99.99 | | | | | | |
| Alarms | Two – programmable set points from 0.0 to 2500.0Ω | | | | | | |
| Memory | Stores up to 1500 test results; Data in memory can be reviewed on the instrument display, on a PC or via direct printout | | | | | | |
| Power Source | Rechargeable 6V, 8.5Ah NiMH battery pack (included) | | | | | | |
| Battery Life | Approximately 5000 10A tests | | | | | | |

► FEATURES



cover closed

- Measure from 1μΩ (0.1μΩ resolution) to 2500.0Ω
- Test current selection of 1mA, 10mA, 100mA, 1A and 10A
- RTD temperature probe to check tested sample (optional)
- Selectable metal types
- Automatic and manual temperature correction
- Two programmable alarm set points
- Stores up to 1500 test results
- Selectable inductive or resistive test modes
- Automatic multiple test mode (multiple tests without pressing the test button)
- Large multi-line electroluminescent display
- Local or remote test setup and control
- Internal rechargeable batteries conduct up to 5000 – 10A tests
- Rugged, double insulated waterproof case
- Includes RS-232 to USB 2.0 cable and AC line cord
- Includes FREE DataView® software for data storage, real-time display, analysis and report generation

► ACCESSORIES

Kelvin clips, set of two

Catalog #1017.84 (included)

(10A – Hippo) 10 ft

Catalog #2118.70 (optional)

(10A – Hippo) 20 ft

Kelvin clips, set of two (optional)

Catalog #2118.79

(1-10A) 10 ft

Catalog #2118.80

(1-10A) 20 ft

Kelvin probes, set of two (optional)

Catalog #2118.77

(10A – spring loaded) 10 ft

Catalog #2118.78

(10A – spring loaded) 20 ft

Kelvin probes pistol grip, set of two (optional)

Catalog #2118.75

(10A – spring loaded) 10 ft

Catalog #2118.76

(10A – spring loaded) 20 ft

Kelvin probes, set of two (optional)

Catalog #2118.73

(1A – spring loaded) 10 ft

Catalog #2118.74

(1A – spring loaded) 20 ft

RTD Temperature Probe (optional)

Catalog #2129.95

RTD probe plugs into faceplate

Catalog #2129.96

RTD probe w/7 ft extension cable

USB Stick

Supplied with DataView® software and user manual

| CATALOG NO. | DESCRIPTION |
|-------------------------------|---|
| 2129.81 | 10A Micro-Ohmmeter Model 6250 |
| Accessories (Optional) | |
| 1017.84 | Kelvin Clips 10 ft (10A – Hippo) |
| 2118.70 | Kelvin Clips 20 ft (10A – Hippo) |
| 2118.73 | Kelvin Probes 10 ft (1A, Spring Loaded) |
| 2118.74 | Kelvin Probes 20 ft (1A, Spring Loaded) |
| 2118.75 | Kelvin Probes Pistol Grip (10A – spring loaded), set of two, 10 ft |
| 2118.76 | Kelvin Probes Pistol Grip (10A – spring loaded), set of two, 20 ft |
| 2118.77 | Kelvin Probes (10A – spring loaded), set of two, 10 ft |
| 2118.78 | Kelvin Probes (10A – spring loaded), set of two, 20 ft |
| 2118.79 | Kelvin Clips 10 ft (1-10A) Replacement for Cat #2118.71 |
| 2118.80 | Kelvin Clips 20 ft (1-10A) Replacement for Cat #2118.72 |
| 2119.45 | Cable, PC RS-232, DB9 F/F 6 ft Null Modem Cable |
| 2129.95 | RTD Temperature Probe (plug into faceplate for ambient temperature) |
| 2129.96 | RTD Temperature Probe with 7 ft extension cable |

