

THREADED THERMOWELLS

REOTEMP Threaded Thermowells make it possible to remove an instrument without dropping pressure or losing contents of the process. Thermowells also protect the instrument from getting bent by the process media. Threaded thermowells are perfect for applications that require infrequent replacement and are commonly installed on smaller pipes or vessels. They are best suited for non-corrosive media. REOTEMP threaded thermowells are machined from solid bar stock.



Threaded




FEATURES / BENEFITS

- Machined from Solid Material
- Protects Your Instrument from the Process
- Easy Removal of Instrument for Calibration or Replacement

OPTIONS

- Wake Frequency Calculation
- Hydrostatic Test
- NACE Certified
- Material Certificate
- Special Marking (Stamping)
- Plug & Chain
- PMI



STANDARD DIMENSIONS

Stem "A"	Standard "U"	Lagging "U"	Overall Length
2.5"	1.625"	N/A	2.875"
4"	2.5"	N/A	4.25"
6"	4.5"	2.5"	6.25"
9"	7.5"	4.5"	9.25"
12"	10.5"	7.5"	12.25"

THREADED THERMOWELLS




Visit reotemp.com


- ✓ Check Stock
- ✓ Get Price
- ✓ Configure Part #
- ✓ Generate a Custom Engineering Drawing

HOW TO ORDER: Choose options to build a part number. For example: **ST6316-ML**


TYPE	"A" STEM LENGTH	MATERIAL	PROCESS CONNECTION	SHANK	BORE DIAMETER	OPTIONS
ST = Threaded LG = Threaded Lagging	2.5 = 2.5" 4 = 4" 6 = 6" 9 = 9" 12 = 12"	304 = 304SS 316 = 316SS 316L = 316L SS B = Brass C = Carbon Steel (1018) G = Hastelloy B H = Hastelloy C M = Monel/A400 T = Titanium Y = Inconel 600 A = Alloy 105 Carbon Stainless Steel D = Alloy 20 5 = F5 Alloy P = PTFE Coated 316SS N = F22 Alloy Other materials available. Contact REOTEMP customer service for more information.	" " = 3/4" NPT (std.) 1 = 1" NPT H = 1/2" NPT 2 = 1.5" NPT	" " = Stepped (std.)* T = Tapered S = Straight *Not available with .385 bore.	" " = .260 (std.) B3 = .385 B5 = .515 I3 = 3/4" NPT Internal Thread Other bore and internal thread sizes available.	EP = External Pressure Test IT = Internal Pressure Testing (5 min. test) MT = Material Certificate ML = Mill Certificate MR = NACE MR-01-75 Approval M3 = NACE MR-01-03 Approval PM = Positive Material Identification (PMI) P4 = SS 304 Plug & Chain P6 = SS 316 Plug & Chain PB = Brass Plug & Chain R2 = Special Surface Finish (Ra 20 max) T1 = Tantalum Coating/ Halar Coating T2 = Teflon Coating (Specify PFA or PTFE) T3 = Tungsten Carbide Coating TM = Special Marking (Stamping) TS = SS Tag (attached) WK = Wake Frequency Calculation



All dimensions are in inches.



All dimensions are in inches.



All dimensions are in inches.

STEPPED SHANK			
Bore Dia.	Ext. Thread Size	Shank Dia. "Q1" (U>2.5)	Shank Dia. "Q2"
.260"	1/2" NPT	.625"	.500"
.260"	3/4" NPT	.750"	.500"
.260"	1" NPT	.875"	.500"

STRAIGHT SHANK			
Bore Dia.	Ext. Thread Size	Shank Dia. "Q" (U≤2.5)	Shank Dia. "Q" (U>2.5)
.260"	1/2" NPT	.500"	.625"
.260"	3/4" NPT	.500"	.625"
.260"	1" NPT	.750"	.875"
.385"	1/2" NPT	.680"	.680"
.385"	3/4" NPT	.766"	.766"
.385"	1" NPT	.875"	.875"

TAPERED SHANK			
Bore Dia.	Ext. Thread Size	Shank Dia. "Q1"	Shank Dia. "Q2"
.260"	1/2" NPT	.680"	.625"
.260"	3/4" NPT	.875"	.625"
.260"	1" NPT	1.062"	.625"
.385"	1/2" NPT	.680"	.625"
.385"	3/4" NPT	.875"	.766"
.385"	1" NPT	1.062"	.766"