

Part No.

QTHA-KIT0-SS

5 pc Quick-test fitting kit - 1/8" MNPT, 1/8" FNPT, 1/4" MNPT, 1/4" FNPT, 1/4" Tube adapters, S.S.

A set of the most commonly used stainless steel adapters make calibrating in the field easier



QTHA-KIT0-SS

Included Items

- 1/8" Male NPT adapter, S.S. - 1/8" male NPT x male Quick-test, no check-valve, S.S. (QTHA-1MS0)
- 1/8" Female NPT adapter, S.S. - 1/8" female NPT x male Quick-test, no check-valve, S.S. (QTHA-1FS0)
- 1/4" Male NPT adapter, S.S. - 1/4" male NPT x male Quick-test, no check-valve, S.S. (QTHA-2MS0)
- 1/4" Female NPT adapter, S.S. - 1/4" female NPT x male Quick-test, no check-valve, S.S. (QTHA-2FS0)
- 1/4" tube adapter, S.S. - 1/4" tube fitting x male Quick-test, no check-valve, S.S. (QTHA-2TS0)

Specs/Attributes

Max Pressure	5000 PSI / 350 bar / 35 MPa
Materials	Stainless Steel
Seal Materials	Buna-N
Number of Adapters	5
Number of Hoses	0
Country of origin	USA

1/8" Male NPT adapter, S.S. QTHA-1MS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C

1/8" Male NPT adapter, S.S. QTHA-1MS0

Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Connector End 1	1/8" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Dimensions	H: 1.2 in (3.05 cm) x W: 0.56 in (1.42 cm)

1/8" Female NPT adapter, S.S. QTHA-1FS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Seal Materials	Buna-N
Wrench Size	5/8 In 16 mm
Connector End 1	1/8" Female NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Dimensions	H: 1.38 in (3.51 cm) x W: 0.62 in (1.57 cm)

1/4" Male NPT adapter, S.S. QTHA-2MS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Dimensions	H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm)

1/4" Female NPT adapter, S.S. QTHA-2FS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel

1/4" Female NPT adapter, S.S. QTHA-2FS0

Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Seal Materials	Buna-N
Wrench Size	3/4 In 19 mm
Connector End 1	1/4" Female NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Dimensions	H: 1.57 in (3.99 cm) x W: 0.75 in (1.91 cm)

1/4" tube adapter, S.S. QTHA-2TS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Seal Materials	Buna-N
Connector End 1	1/4" Male Tube Fitting
Connector End 2	Male Quick-test
Dimensions	H: 1.47 in (3.73 cm) x W: 0.56 in (1.42 cm)