

4, 5 and 6-Wire eurofast® Cordsets, "S" Style, Shielded

- Straight Female Connector
- Shield to Coupling Nut
- NEMA 1, 3, 4, 6P and IEC IP 68 Protection



Housing Style	Part Number	Cable	Features	Pinout
	RKS 4.4T-*	AWM PVC Grey 4x22 AWG 105°C, 250 V, 4 A 7.3 mm OD Cable #RF50729-*M†	RFI/EMI	1. BN 2. WH 3. BU 4. BK
	RKS 4.4T-*/S90	AWM PUR Grey 4x22 AWG 105°C, 250 V, 4 A 7.2 mm OD Cable #RF50810-*M†		
	RKS 4.4T-*/S824	PLTC PVC Grey 4x22 AWG 105°C, 250 V, 4 A 7.3 mm OD Cable #RF50823-*M†	RFI/EMI Tray rated	
	RKS 4.5T-*	AWM PVC Grey 5x22 AWG 105°C 250 V, 4 A 7.3 mm OD Cable #RF50713-*M†	RFI/EMI	1. BN 2. WH 3. BU 4. BK 5. GY
	RKS 6T-*	AWM PVC Grey 6x24 AWG 105°C, 60 VAC/75 VDC, 2 A 7.3 mm OD Cable #RF50814-*M†	RFI/EMI	1. BN 2. WH 3. BU 4. BK 5. GY 6. PK

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "RKS .."; "RKSV .." indicates 316 stainless steel.

† See Section N for **reelfast**® cable information.

4, 5 and 6-Wire eurofast® Cordsets, "S" Style, Shielded

- Straight Male Connector
- Shield to Coupling Nut
- NEMA 1, 3, 4, 6P and IEC IP 68 Protection



Housing Style	Part Number	Cable	Features	Pinout
	RSS 4.4T-*	AWM PVC Grey 4x22 AWG 105°C, 250 V, 4 A 7.3 mm OD Cable #RF50729-*M†	RFI/EMI Shielding Tied to Coupling Nut	1. BN 2. WH 3. BU 4. BK
	RSS 4.4T-*/S90	AWM PUR Grey 4x22 AWG 105°C, 250 V, 4 A 7.2 mm Cable #RF50810-*M†		
	RSS 4.4T-*/S824	PLTC PVC Grey 4x22 AWG 105°C, 250 V, 4 A 7.3 mm OD Cable #RF50823-*M†	RFI/EMI Shielding Tied to Coupling Nut, Tray Cable Rated	
	RSS 4.5T-*	AWM PVC Grey 5x22 AWG 105°C, 250 V, 4 A 7.3 mm OD Cable #RF50713-*M†	RFI/EMI Shielding Tied to Coupling Nut	1. BN 2. WH 3. BU 4. BK 5. GY
	RSS 6T-*	AWM PVC Grey 6x24 AWG 105°C 60 VAC/75 VDC, 2 A 7.3 mm OD Cable #RF50814-*M†	RFI/EMI Shielding Tied to Coupling Nut	1. BN 2. WH 3. BU 4. BK 5. GY 6. PK

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "RSS .."; "RSSV .." indicates 316 stainless steel..

† See Section N for **reelfast**® cable information.