

6-Wire Receptacles, Front Mount, 1/2-14 NPSM Threads

- NEMA 1, 3, 4, 6P
- IEC IP67 Protection



Housing Style	Female Part Number	Male Part Number	Features	Pinout	
RKF .. Typical panel cutout 22.5 mm	RKF 61-*M	RSF 61-*M	6x18 AWG, 105°C, 600 V, 8 A, standard threads	1. GN 2. WH 3. BU 4. Gy 5. YE 6. BN	Female
	RKF 61-*M/S849	RSF 61-*M/S849	6x22 AWG, 105°C, 300 V, 5 A, standard threads		
RSF .. Typical panel cutout is 22.5 mm	RKF 66-*M	RSF 66-*M	6x16 AWG, 105°C, 600 V, 8 A, heavy duty	1. WH 2. RD 3. GN 4. OG 5. BK 6. BU	Male
	RKF 66-*M/S849		6x22 AWG, 105°C, 300 V, 5 A, heavy duty		
	RKF 68-*M	RSF 68-*M	6x18 AWG, 105°C, 600 V, 8 A, heavy duty		

Standard lead length is 0.3 Meters. Consult factory for other lengths.

** Standard housing material is nickel plated brass.. "RSF .."; "RSFV .." indicates stainless steel housing, and "RSFK .." indicates nylon housing.

For locknuts to be included, add "W/LN" to the end of the part number.

To specify PVC jacketed cable, add "/S717" to the end of the part number.