

**2, 4 and 5-Wire Receptacles, Front Mount, PG 9 Threads**

- NEMA 1, 3, 4, 6P
- IEC IP68 Protection
- 250 V, 4 A



Housing Style	Female Part Number	Male Part Number	Features	Pinout
<p><b>FK(N) ..*</b></p> <p>Typical panel cutout is 15.2 mm.</p>	FK 4.2-*	FS 4.2-*	2x22 AWG, 105°C, mates with 2-pin Cordsets	<p>1. N/C 2. N/C 3. BN 4. BU</p> <p><b>Female</b></p>
	FK 4.21-*	FS 4.21-*	2x22 AWG, 105°C, mates with 2-pin Cordsets	<p>1. BN 2. BU 3. N/C 4. N/C</p>
	FK 4.22-*	FS 4.22-*	2x22 AWG, 105°C, mates with 2-pin Cordsets	<p>1. BN 2. N/C 3. BU 4. N/C</p>
	FK 4.4-*	FS 4.4-*	4x22 AWG, 105°C, mates with 4-pin cordsets	<p>1. BN 2. WH 3. BU 4. BK</p> <p><b>Male</b></p>
	FK 4.4-*/S613	FS 4.4-*/S613	4x18 AWG, 105°C, mates with 4-pin cordsets	<p>1. BN 2. WH 3. BU 4. BK</p>
	FK 4.4-*/S621	FS 4.4-*/S621	4x18 AWG, 105°C, mates with 4-pin cordsets	<p>1. GY1 2. GY2 3. GY3 4. GY4</p>
	FK 4.5-*	FS 4.5-*	5x22 AWG, 105°C, mates with 5-pin Cordsets	<p>1. BN 2. WH 3. BU 4. BK 5. GY</p> <p><b>Female</b></p>
	FK 4.5-*/S627	FS 4.5-*/S627	5x20 AWG, 105°C, mates with 5-pin cordsets	<p>1. BN 2. WH 3. BU 4. BK 5. Drain</p> <p><b>Male</b></p>
<p><b>FS(N) ..*</b></p> <p>Typical panel cutout is 15.2 mm.</p>	FK 4.5-*/S653	FS 4.5-*/S653	4x22 AWG, Drain, 105°C, 5.1 mm OD, mates with 5-pin cordsets, 4 conductors PVC foil shielded with drain wire to pin 5	<p>1. GN 2. WH 3. OG 4. BK 5. RD</p>
	FKN 5-*	FSN 5-*	5x22 AWG, 105°C	

\* Length in meters. Standard Lead length is 0.5 Meters. Consult factory for other lengths.  
Standard housing material is nickel plated brass "FS.."; "FSV.." indicates stainless steel.  
To specify PVC jacketed cable, add "/S717" to the end of the part number.