



### MODEL 1510

Monitor CO<sub>2</sub>, temperature, and humidity for a healthy environment



### FEATURES

- CO<sub>2</sub>, temperature, and humidity logger
- Free app for Android™ from the Google® Play Store
- Compact and stand-alone: for mounting or portable use
- User-friendly: comfort indicators based on the CO<sub>2</sub>, temperature and humidity levels
- Accurate: complies with the latest standards concerning air quality monitoring
- Quick, simple data download using supplied DataView® software
- On-site calibration test module with adapter, tube and software for adjusting the zero and thresholds

### PRODUCT INCLUDES

- Meter in carrying pouch
- Adapter - US wall to USB
- 6ft USB cable
- 2 AA batteries
- Quick start guide
- User manual and DataView® application software included on USB Drive

CATALOG NO.	DESCRIPTION
2138.08	Air Quality Logger Model 1510 (Gray)
2138.09	Air Quality Logger Model 1510 (White)
<b>Accessories/Replacement - available on website store from <a href="http://www.aemc.com">www.aemc.com</a></b>	
2138.61	Wall Mount Holster (Gray)
2138.62	Desktop Stand (White)
2153.78	Adapter - US Wall Plug to USB
2138.67	Wall Mount Holster (White)

### SPECIFICATIONS

CO <sub>2</sub> Measurement	
Measuring Principle	Non-dispersive infrared (NDIR) technology
Type of Sensor	Double-beam infrared cell sensor
Measurement Range	0 to 5000 ppm
Accuracy (CO <sub>2</sub> )	±50 ppm ±3% of value measured
Response Time, 63%	< 200 seconds
Resolution	1 ppm
Temperature Measurement	
Type of Sensor	CMOS
Units	°C or °F
Measurement Range	14° to 140°F (-10° to 60°C)
Accuracy	±0.1°F (±0.5°C)
Resolution	0.1°F (0.1°C)
Humidity Measurement	
Type of Sensor	Capacitive
Measurement Range	5 to 95% RH
Accuracy	±2% RH
Resolution	0.1% RH
General	
Recording Interval	Programmable from 1 minute to 2 hours
Storage	> 1 million measurements
Alarm	Yes
Backlighting Display, Hold, Min & Max	Yes
Auto Power OFF	Yes (in portable mode only)
Dimensions/Weight	4.92 x 2.58 x 1.26" (125 x 65.5 x 32mm)/ 6.7oz (190g) with batteries
Protection	IP40
Compliance	IEC 61010-1, 50V CAT II - IEC 61326-1
Power Supply	Alkaline batteries: 2 AA or rechargeable battery connection to 120V 60Hz line/USB to wall adapter
Communication	Bluetooth (Class I) wireless communication/USB link; the product is then recognized as a USB drive for easy file transfer
Mounting	Optional padlockable wall mount (padlock is not included), optional desktop stand and tear drop wall hook
DataView® Software	Graphic representation or as table of values, data export, real-time mode calculation of the confinement index with selection of presence periods & report generation