

## **Bimetal Thermometer**





## Part #:

AA0251F23-HVPY

## **Description:**

Industrial Bimetal Dial Thermometer, 3" Dial Back Conn./Reset, 2.5" Stem, 1/2" NPT (fits std. thermowell), -40/160°F, Hi-Vis Dial (High Visibility), Polycarbonate Window

Thermometer Data:	
Dial Size/ Configuration:	3" Dial Back Conn./Reset
Stem Length, "A" :	2.5 in. (64mm)
Stem Dia., "d":	1/4"
Process Connection:	1/2" NPT (fits std. thermowell)
Temperature Range:	-40/160°F
Accuracy:	+/- 1% of full scale
Actuation:	Bimetal coil in stem
Sealing:	Hermetically Sealed per ASME
	B40.3

Options and Accessories:				
	(may not be depicted in drawing)			
Option 1:	Hi-Vis Dial (High Visibility)			
Option 2:	Polycarbonate Window			

Revisions*:	Data ger	erated on:	1/10/2020			
Latest Rev:	x1	Rev. Date:	11/1/2012			
Description:	Initial Release					

\*Revision date applies to all possible data: Individual drawings may not be affected. To obtain current revision, re-generate drawing at www.reotemp.com.

	Part Name: AA0251F23-HVPY							
	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES 64		REOTEMP Instrument Corporation				SEE_ABOVE	
	TOLERANCES ARE:   FRACTIONS DECIMALS ANGLES  ± 1/32	V	REO	TEM	P 10656 Roselle San Diego, CA 9 Phone; (858) 73	2121 USA	JR APPROVED	
File Control	.XX ± .01 .XXX ± .005	INSTRUMENTS Fax: (858) 784-0720				AFFROVED		
BH-AA	Copyright © 2012	SIZE	CAGE CODE		DWG NO.	- O / E		
BC-1A		в   24793		3	SEE_ABOVE			
BS-25	REOTEMP Instruments	SCAL	E: NTS	FILE NA	AME:	SHEET 1	OF 1	