


NETWORK WIRING

PROFIBUS®-PA, On-Machine Passive Junction Boxes

- Multiple Port Configurations Available
- Cast aluminum Housing*
- 7/8" x 1 Bus In/Bus Out Connectors*
- Nickel Plated Brass Connectors Available
- CSA General Purpose
- -40°C to +75°C (-40°F to +167°F)
- IP67, IP68 and IP69k

*(Unless otherwise specified)



Housing Style	Part Number	Specifications	Pinouts
	JBBS-48-E613	M12x1 Bus-in/Bus-out plus 6 drops	
	JBBS-48-E813	M12x1 Bus-in/Bus-out plus 8 drops	
	JBBS-48-M613	7/8"-16UN Bus-in/Bus-out plus 6 drops	
	JBBS-48-M813	7/8"-16UN Bus-in/Bus-out plus 8 drops	
	JBBS-48SC-E413	M12x1 Bus-in/Bus-out plus 4 drops, short circuit protection	
	JBBS-48SC-E613	M12x1 Bus-in/Bus-out plus 6 drops, short circuit protection	
	JBBS-48SC-E813	M12x1 Bus-in/Bus-out plus 8 drops, short circuit protection	
	JBBS-48SC-M413	7/8"-16UN Bus-in/Bus-out plus 4 drops, short circuit protection	
	JBBS-48SC-M613	7/8"-16UN Bus-in/Bus-out plus 6 drops, short circuit protection	
	JBBS-48SC-M813	7/8"-16UN Bus-in/Bus-out plus 8 drops, short circuit protection	